

# S3000-16X

## 16-Port Fiber Switch



### Features

- > 16\*100Mbps SFP fiber ports and 2\*1000Mbps Combo ports
- > IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- > Support WEB, SNMP (v1/v2c), link aggregation
- > Port isolation, speed limit, mirroring, 802.1Q VLAN
- > Anti-MAC address flooding
- > IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards

### Technical Specifications

Model	S3000-16X
Physical Port	16 * 100Mbps SFP fiber ports 2 *1000Mbps Combo ports (optical or electrical ) 1 Console port
Exchange mode	Store & forward

## S3000-16X

Application Humidity	10%—90%
Power	AC 90~264V
Power consumption	≤15W
High&Low temperature	- 10℃~55℃
Weight	3.5kg
Dimension(W × D×H)	440mm×43.5mm×300mm

---

### Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

\*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.