
 Winstars Product Specifications		Version	V1.1			
		Page	1/1			
Model	WS-UG69DK7	Date	2017.03.10			
Name	USB-C 4K Ultra HD Universal Docking Station	Writer	chen			
Picture 图片		Features: 特点				
		1. USB3.1Gen1 Type-C and Standard-A connectors compatible both Type-C and Type-A Laptop 2. Build in USB 3.0 GPU, Plug and Display Certified by DisplayLink 3. 2 x DP++ (Dual Mode DP1.2) and 2 x HDMI (Version 2.0) support resolution up to (4K)4096 x 2160p6 4. Support resolution 5k)5120 x 2880p60 when only using one DP++ port 5. Supports DP MST (Multi-Streaming) which allows for the use of daisy-chained DP monitors, or port expansion to up to 8 1080p monitors 6. Support Extend and Mirror Video Mode. 5.1 Channel surround-sound through Display Port interface 7. Gigabit Ethernet network RJ-45 backward 10/100 Ethernet 8. Audio Line-out Jack for Earphone and Line-In Jack Microphone 9. 4 x Type-A + 2 x Type-C ports compatible all USB 3.0 and USB 2.0 devices,				
Title 标题		Package content 标配				
USB-C 4K Ultra HD Multiple-Display Universal Docking Station for Type-C and Type-A Desktop or Laptop PC		(Full-Screen Video Playback) CPU Processor: Core i7 RAM: 4GB				
Description 介绍		SYSTEM REQUIREMENT: 系统配置				
Unique Aluminum Vertical design, The new USB Type-C connector works seamlessly with this Ultra HD 4K Universal Docking Station. It can connect to any host with Standard A or Type C connectors providing a fully backward-compatible and future-proof docking solution. Allow you to connect up to two additional monitors and eleven accessories through a single USB cable. Including the latest drivers for compatibility with Windows 10, 8.1 and 7 or Apple Mac OS		1x USB-C Universal Docking station 1x USB3.0 C to C Cable 1x USB3.0 A to C Cable 1x User Manual 1x Software Installation CD 1x DC20V Certified Power Adapter				
Specification 规格						
Hardware 硬件		Functions 功能		Exterior 外观		
Ports	1 x Upstream Type-C port; DC Jack; 2 x DP and 2 x HDMI; 4 x USB3.0 Type-A ports and 2 x USB3.1 Gen.1 Type-C ports; Earphone / Microphone Jack; RJ45; LED	Working Standards	1. Hub running at USB3.0 speed 2. Either DP or HDMI provided 2 video o/p, resolution Max. 4096 x 2160p60 3. Ethernet running at Gigabit 4. 2.0 Audio	Color	Black	
Button	Nil			Power Cable	1000MM black	
LED	Blue Color LED			Data Cable	Black	
Chipset	DL6950 VL813 GL3523					
Flash	8MB	Operating System Support	Microsoft Windows & Apple Mac OS			
SDRAM	256Mx16 DDR3 x 2pcs, 8GB					
Power Supply	DC20V	Max Pixels	5120*2880p60			
Power Plug	US/EU/UK or by request	Max charging current(A)				
Power Consumption	3W					
Rated Voltage/ requency /current	100-240 Va.c. 50/60Hz, 0.2A Max , CLASSII					
Dimensions 尺寸		Certification 证书				
Unit Dimensions	150 X 80 X 200MM (L x H x W)	CE-EMC	Design in but Cert. by request			
Weight	裸机450g; 成品889.9g;	CE-RTTE	*****			
Housing Material	Aluminum	CE-LVD	*****			
Shell color	Apple Gray	FCC DOC	Design in but Cert. by request			
Package Dimensions	230 x 160 x 120(L x H xW) primary setting	FCC ID	*****			
Environmental 环境		ROHS	Design in but Cert. by request			
Operating Temperature	0°C~40°C	Reach	Design in but Cert. by request			
Storage Temperature	-10~70°C	3C	Design in but Cert. by request			
Relative Humidity(Operational)	10%~90%,noncondensing	Others 其他				
Relative Humidity(Storage)	10%~90%,noncondensing	Method	See User Manual			
Drop test (1 Meters)	5 st	Performance	See Test Report			
Cycle work (hours)	24H	Reliability	See Test Report			

Interface	5K	4K	2K	1K	MST	
	5120x2880p60	4096x2160p60 3840x2160p60	2560x1600p60 2560x1440p60	FHD	2K	FHD
DP1	✓	✓	✓	✓	2x	4x
DP2		✓	✓	✓	2x	4x
HDMI1		✓	✓	✓	NA	NA
HDMI2		✓	✓	✓	NA	NA

